



## Features / Benefits

- Eco-friendly R10A Refrigerant
- Digital Microprocessor Controller
- UL508a Electric Panel
- High Performance Scroll Compressors
- 40 psi Centrifugal Pump
- Steel Storage Tank
- Indoor/Outdoor Rated

## Options

- High Pressure Pump
- Stainless Steel Tank w/Non-ferrous Water Circuit
- Low Ambient Package for -4°F
- Open/Close Exposure Tank
- Remote Controller
- Condenser Coil Coating

## Product Specifications

CAPACITIES		031	051
Cooling Capacity	ton	3.2	4.6
<i>Capacity based on 45°F water outlet temp.; 10°F delta t @ 95°F ambient temperature</i>			
BTU/hr		38,400	55,200
Tank Volume	gal	30.4	30.4
DIMENSIONS		031	051
Width	in	26	26
Depth	in	52	52
Height	in	56	56
Weight	lbs	721	765
ELECTRICAL		031	051
Volts		460	460
Phase		3	3
Hertz		60	60
FLA		10	13
MISC SPECS		031	051
Refrigerant		R410A	R410A
Protection Class		IP 54	IP 54
Water Flow (min/max)	gpm	2.2/21.1	2.2/21.1
# of Fans		1	1
Total air flow	cfm	4414	4179
Connection Size	npt	1"	1"