



Features / Benefits

- Eco-friendly R10A Refrigerant
- Digital Microprocessor Controller
- UL508a Electric Panel
- High Performance Scroll Compressors
- 40 psi Centrifugal Pump
- Steel Storage Tank
- Indoor/Outdoor Rated

Options

- High Pressure Pump
- Stainless Steel Tank w/Non-ferrous Water Circuit
- Low Ambient Package for -4°F
- Open/Close Exposure Tank
- Remote Controller
- Condenser Coil Coating

Product Specifications

CAPACITIES		702	802
Cooling Capacity	ton	46.1	53.5
<i>Capacity based on 45°F water outlet temp.; 10°F delta t @ 95°F ambient temperature</i>			
BTU/hr		553,200	642,000
Tank Volume	gal	179	179
DIMENSIONS		702	802
Width	in	50	50
Depth	in	140	140
Height	in	85	85
Weight	lbs	4700	4800
ELECTRICAL		702	802
Volts		460	460
Phase		3	3
Hertz		60	60
FLA		127	144
MISC SPECS		702	802
Refrigerant		R410A	R410A
Protection Class		IP 54	IP 54
Water Flow (min/max)	gpm	65.6/206.9	65.6/206.9
# of Fans		3	3
Total air flow	cfm	41672	42370
Connection Size	npt	3"	3"