

INDUSTRIAL WATER CHILLER

ACCPS-201/251/301/351



Product Specifications

CAPACITIES		201	251	301	351
Cooling Capacity	ton	15.1	16.8	20	22.3
Capacity based on 45°F water outlet temp.; 10°F delta t @ 95°F ambient temperature					
BTU/hr		181,200	201,600	240,000	267,600
Tank Volume	gal	93	93	93	93

DIMENSIONS		201	251	301	351
Width	in	35	35	35	35
Depth	in	89	89	89	89
Height	in	82	82	82	82
Weight	lbs	2250	2250	2346	2400

Features / Benefits

- Eco-friendly R410a Refrigerant
- Digital Microprocessor Controller
- UL508a Electric Panel
- High Performance Scroll Compressors
- 40 psi Centrifugal Pump
- Steel Storage Tank
- Indoor/Outdoor Rated

ELECTRICAL		201	251	301	351
Volts		460	460	460	460
Phase		3	3	3	3
Hertz		60	60	60	60
FLA		42	48	55	68

Options

- High Pressure Pump
- Stainless Steel Tank w/Non-ferrous Water Circuit
- Low Ambient Package for -4°F
- Open/Close Exposure Tank
- Remote Controller
- Condenser Coil Coating

MISC SPECS		201	251	301	351
Refrigerant		R410a	R410a	R410a	R410a
Water Flow (min/max)		IP 54	IP 54	IP 54	IP 54
Water Flow (min/max)	gpm	15.4/84.5	15.4/84.5	29/149.7	29/149.7
# of Fans		2	2	3	3
Total air flow	cfm	11595	11595	15421	15421
Connection Size	npt	2"	2"	2"	2"