



## Features / Benefits

- Eco-friendly R410a Refrigerant
- Digital Microprocessor Controller
- UL508a Electric Panel
- High Performance Scroll Compressors
- 40 psi Centrifugal Pump
- Steel Storage Tank
- Indoor/Outdoor Rated

## Options

- High Pressure Pump
- Stainless Steel Tank w/Non-ferrous Water Circuit
- Low Ambient Package for -4°F
- Open/Close Exposure Tank
- Remote Controller
- Condenser Coil Coating

## Product Specifications

| CAPACITIES  |     | 031      | 051      |
|---|-----|----------|----------|
| Cooling Capacity  | ton | 3.2      | 4.6      |
| <i>Capacity based on 45°F water outlet temp.; 10°F delta t @ 95°F ambient temperature</i> |     |          |          |
| BTU/hr  |     | 38,400   | 55,200   |
| Tank Volume   | gal | 30.4     | 30.4     |
| DIMENSIONS  |     | 031      | 051      |
| Width   | in  | 26       | 26       |
| Depth   | in  | 52       | 52       |
| Height  | in  | 56       | 56       |
| Weight  | lbs | 721      | 765      |
| ELECTRICAL  |     | 031      | 051      |
| Volts   |     | 460      | 460      |
| Phase   |     | 3        | 3        |
| Hertz   |     | 60       | 60       |
| FLA   |     | 10       | 13       |
| MISC SPECS  |     | 031      | 051      |
| Refrigerant   |     | R410a    | R410a    |
| Protection Class  |     | IP 54    | IP 54    |
| Water Flow (min/max)  | gpm | 2.2/21.1 | 2.2/21.1 |
| # of Fans   |     | 1        | 1        |
| Total air flow  | cfm | 4414     | 4179     |
| Connection Size   | npt | 1"       | 1"       |